PETITION OF STATE OF MINNE-SOTA, BY JAMES OF MARSHALL, STS COMMISSIONER OF HIGHWAYS FOR THE RIGHT TO MAKE A MINOR ALTERATION OR CHANGE IN COUN-TY DITCH NO. 28, IN ANOKA COUN-TY.

NOTICE OF HEARING

TO ALL PERSONS INTERESTED IN COUNTY DITCH NO. 28, IN ANOKA COUNTY:

YOU AND EACH OF YOU. WILL PLEASE TAKE NOTICE, that the State of Minnesota, by James C. Marshall, of Minnesota, by James C. Marshall, and the State of Minnesota Statutes filed a Petition with the County Auditor of Anoka County, pursuant to Section 161.28 of Minnesota Statutes 1959, praying that he be allowed to make a minor alteration or change in make a minor alteration or change in the County Ditch No. 28. That attached to said Petition now on file with the county Auditor are plan and profile sneets showing said minor alteration or change petitioned for That the portion of said County Ditch No. 28 as now located which is proposed to be changed or altered is described as follows:

Approximate Present Location of Portion of County Ditch No. 28:

From a point on the north line of section 32, township 33 north, range 23 west, distant 129.3 feet east of the north quarter corner thereof, run southerly at an angle of 86°36 run southerly at an angle of 86°36 run southerly at an angle of 86°36 run southerly at an angle of section line (when measured from east to south) for a distance of 108.2 feet; thence defect to the left at an angle of 38°30 and run southeasterly for a distance of 500 feet; thence deflect to the line to be described; thence run northeasterly on the last described course for a distance of 35° feet; thence deflect to the right at an angle of 35°00 and run northerly and parallel to Trunk Highway No. 65 in place for a distance of 3115.0 feet and there terminating.

Approximate Proposed Location of Portion of County Ditch No. 28:

From a point on the north line of section 32 township 33 north, range 23 west, distant 1293 feet east of the north quarter corner thereof, run southerly at an angle of 86°36′ run southerly at an angle of 86°36′ run southerly at an angle of 86°36′ run southerly at an angle of clistance of 108.2 feet; thence deflect to the left at an angle of 156°15′ and run southerly for a 155°15′ and run southerly for a 155°15′ and run southerly for a distance of 180 feet; thence deflect to the point of the north point of the line to be described; thence run northerly and parallel to the north bound roadway for a distance of 36°50′ feet way for a distance of 180° feet of 26°30′ feet thence run northerly and parallel to the north bound roadway for a distance of 36°50′ feet

Approximate Present Location of Fortion of County Ditch No. 28:

section 5, township 32 north, range section 5, township 32 north, range 23 west, distant 125.1 feet east of the morth quarter thereof, run fine north quarter thereof, run factoristic feet east of the north quarter thereof, with southerly at an angle of 84.16 with southerly at an angle of 852.20" to the right at an angle of 852.20" to the right at an angle of 852.20" and run southerly for a distance of shad run southerly for a distance of 110 feet; thence deflect to the left at an angle of 90.00 and run easterly for a distance of 100 feet; thence effect to the last described course for a distance of 110 feet; thence deflect to the right at an angle of 48.20 and run northwesterly for a distance of 125 feet; thence deflect to the right at an angle of 32.00 and run northwesterly for a distance of 265 feet; thence deflect to the left at an angle of 43.00 and run northwesterly for a distance of 265 feet; thence deflect to the left at an angle of 43.00 and run single of 43.00 and run morthwesterly for a distance of 265 feet; thence deflect to the left at an angle of 43.00 and run single of 43.00 and run morthwesterly for a distance of 265 feet; thence deflect to the left at an angle of 43.00 and run westerly for a distance of 265 feet; thence deflect to the left at an angle of 43.00 and run westerly for a distance of 25 feet; thence deflect of the left at an angle of 43.00 and run westerly for a distance of 25 feet; thence deflect of the left at an angle of 43.00 and run westerly for a distance of 25 feet; thence deflect of the left at an angle of 43.00 and run westerly for a distance of 25 feet; thence deflect of the left at an angle of 43.00 and run westerly for a distance of 25 feet; thence deflect of the left at an angle of 43.00 and run westerly for a distance of 105 feet and there terminating.

Approximate Proposed Location of Portion of County Ditch No. 28:

From a point on the north line of section 5, township 32 north, range section 5, township 32 north, range section 5, township 32 north set east of the north quarter thereof, run southerly at an angle of 84°.6° with said north section line (when with said north section line (when with said north section line (when the satured of 515.1 feet: thence deflect to the right at an angle of 6°52'20° to the right at an angle of 90°00 and run southerly for a distance of 1113.0 feet; thence deflect to the left at an angle of 90°00 and run easterly for a distance of 100 feet the point of beginning of the line to be described; thence run westerly on the last described course for a distance of 40 feet; thence deflect to the right at an angle of 90° and run northeast; thence deflect to the right at an angle of 90° and run northeast; way for a distance of 1238.0 feet; way for a distance of 1238.0 feet; thence deflect to the right at an angle of 50°00 and run northeast; erly for a distance of 45 feet and the parallel to the north bound road-parallel to the n

From a point on the north line of section 5, township 32 north, range 23 west, distant 125.1 feet east of the north quarter corner thereof, run southerly at an angle of 84°16 with said north section line (when with said north section line (when measured from east to south) for a distance of 425 feet; thence deflect to the left at an angle of 120°00° and run northeasterly for a distance of 95 feet to the point of beginning of the line to be described; thence run southwesterly on the last described course for a distance of 27°00° and run westerly for a distance of 35°00° and run westerly for a distance of 35°00° and run southwesterly for a distance of 80° feet; thence of 80° feet and there terminating;

together with the following portion of County Ditch No. 28:

From a point on the north line of said section 5, distant 125.1 feet east of the north quarter corner thereof, run southerly at an angle of 84°16' with said north section line (when measured from east to south) for a distance of 210 feet; thence deflect to the right at an angle of 90°00' and run westenly for a distance of 255 feet to the for a distance of 265 feet to the point of beginning; thence deflect to the standard run southeasterly for a distance of 90 feet; thence deflect to the right at an angle of 45°00' and run southeasterly for a distance of 90 feet; thence deflect to the right at an angle of 45°00' and run southerly for a distance of 230 feet; thence deflect to the left at an angle of 90°00' and run easterly for 25 feet and there terminating.

Approximate Proposed Location of a Portion of County Ditch No. 28:

From a point on the north line of section 5, township 32 north range 23 west, distant 125.1 feet east of the north quarter corner thereof, run southerly at an angle of 84° 16" with said north section line for a distance of 520 feet; thence defect to the left at an angle of 85°30" and run northeasterly for a distance of 75 feet to the point of 55° 20" in the line to be described; thence run southwesterly rorbed; thence run southwesterly for a distance of 315 feet; thence defect to the left at an angle of 95°00" and run southwasterly for a distance of 20 feet; thence deflect to the left at an angle of 95°00" and run southwasterly for a distance of 20 feet; thence deflect to the iright at an angle of 190° and run southwasterly for a distance of 40 feet and there terminating:

together with the following portion of County Ditch No. 28:

From a point on the north line of said section 5. distant 125.1 feet east of the north quarter conner thereof, run southerly at an angle of 84.16" with said north section line for a distance of 210 feet; thence deflect to the right at an angle of 90.00" and run westerly for a distance of 265 feet to the point of beginning of the line to be described; thence deflect to the left at an angle of 125.90° and run southeasterly for a distance of 25 feet; thence deflect to the right at an angle of 125.90° and run southeasterly for a distance of 273 feet; thence 25.00° and run southeasterly for a distance of 273 feet and there terminating.

YOU WILL FURTHER TAKE NO-TICE, that said Petition will be presented to the County Board of Anoka County, in the Court House in Anoka, Minnesota, on the 6th day of May, 1963, at 2 o'clock P.M., at which time all persons interested in said ditch system may appear and be heard and present arguments for or against the granting of said Petition.

KENNETH W. CAMPBELL County Auditor Anoka County

(Published in the Anoka Union Mar. 29, Apr. 5 & 12, 1963)